



Technical Data Sheet.

Permafleet® VHS Non-Sanding Surfacer 5620

Economical, stable 2K VHS wet-on-wet surfacer for commercial vehicles

Permafleet VHS Non-Sanding Surfacer 5620 is a high-quality 2K high solids surfacer based on acrylic resins.

- For efficient wet on wet application.
- Has a very high solids content.
- Offers high coverage.
- Achieves good topcoat holdout.



For professional use only!

Spies Hecker simply closer.



An Axalta Coating Systems Brand

Permafleet® VHS Non-Sanding Surfacer 5620


Product preparation - application STANDARD WET ON WET



It is strongly recommended to use appropriate personal protection equipment during application to avoid respiratory, skin and eye irritation.



Steel, galvanised steel or soft aluminium, sanded and cleaned and coated with Wash Primer
Coil coated, sanded and cleaned
Glass fibre reinforced polyester substrates, free of release agents, sanded and cleaned.
Old or original paintwork well sanded and cleaned.
Surfaces pretreated with 2K polyester products and then finely sanded and cleaned.
OEM Primer (e-coat), sanded and cleaned.



Surfacer		Hardener		Reducer	
Volume	Weight	Volume	Weight	Volume	Weight
3	100	1	21	35 %	23
5620		3265 3270 3275		6110 6120 6130	



Pot life at 20°C: 1 hr 30 min




	Spray nozzle	Spray pressure	
Compliant	1.3 - 1.5	2 - 2.5 bar	inlet pressure
HVLP	1.3 - 1.5	0.7 bar	atomisation pressure
Membrane pump	1.1	2.5 - 3 bar	atomisation pressure
Membrane pump	1.1	0.8 - 1.2 bar	material pressure

see manufacturer's instructions



1 coat

final flash-off: 30 min



Permafleet 2K Topcoats 630/670/675
Permahyd Hi-TEC Base Coat 480 / Permahyd Base Coat 280/285

VOC compliant

2004/42/IIB(c)(540) 540: The EU limit value for this product (product category: IIB(c)) in ready to use form is maximum 540 g/l of VOC. The VOC content of this product in ready to use form is maximum 540 g/l.

Permafleet® VHS Non-Sanding Surfacer 5620

Products

Permafleet® VHS Non-Sanding Surfacer 5620

Permafleet® VHS Hardener 3265 fast

Permafleet® VHS Hardener 3270

Permafleet® VHS Hardener 3275 slow

PERMAFLEET REDUCER 6110 FAST

Permafleet® Reducer 6120

Permafleet® Reducer 6130 slow


Product mix




Mixing ratios with special agents are available in the productmix table on Phoenix and in the specific TDS.

The choice of hardener and Reducer should be made according to application temperature and size of repair.

3265	Accelerated fast hardener for small panels or for design work (stripes) 20-25°C.
3270	Standard hardener for all 2K CV products (20-25°C).
3275	Slow hardener for large surfaces and high temperatures (>30°C).
6110	Fast reducer only for small panels/areas (15-20°C).
6120	Standard CV reducer for all CV products. (20 -25°C).
6130	Slow reducer for large surfaces and high temp. (25-30°C), to avoid overspray problems.



DIN 4: 18 - 20 s at 20°C



30 - 40 µm

Theoretical coverage

420 - 430 m²/l at 1 micron dry film thickness

Due to different hardener characteristics and different mixing ratios of the ready-to-use mixture in some TDS versions, the theoretical coverage calculation may vary.

Note: The practical material consumption depends on several factors, e.g. geometry of the object, surface formation, application method, spray gun setting, inlet pressure, etc.



Clean after use with a suitable solventbased guncleaner.

Permafleet® VHS Non-Sanding Surfacer 5620

Remarks

- Material has to be at room temperature (18-25°C) before use.
- Surplus ready for use material should not be returned to original can.
- Sanding needed if dried more than 16 hours at 20°C.
- Mix thoroughly by hand before placing the can on mixing machine.
- Close can of hardener tightly immediately after use, as this product will react with humid air and water and lose its hardening effect.
- Addition of max. 10% Permafleet Mixing Pastes 600 or 20% Permafleet HS Topcoat 670/675 is possible.
- Color Level 2 can be obtained by mixing the white and the dark grey color in a 100:7 ratio by weight.
- 15% Permasolid Elastic Additive 9050 can be added to the product. Mixing ratios are unchanged.

Consult Safety Data Sheet prior to use. Observe the precautionary notices displayed on the container.

All other products referred to in the refinish build up are from our Spies Hecker product range. System properties will not be valid when the related material is used in combination with any other materials or additives which are not part of our Spies Hecker product range, unless explicitly indicated otherwise.

For professional use only! The information provided in this documentation has been carefully selected and arranged by us. It is based upon our best knowledge on the subject at the date of issuance. The Information is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check the information with regard to up-to-dateness and suitability for his intended purpose. The intellectual property in this Information, including patents, trademarks and copyrights, is protected. All rights reserved. The relevant Material Safety Data Sheet and Warnings displayed on the product label need to be observed. We may modify and/ or discontinue operation of all or portions of this Information at any time in our sole discretion, without notice and assume no responsibility to update the Information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.