

Technical Data Sheet.

Permaloid® Silicone Remover 7799



Fast-drying silicone remover for conventional paint materials

Permaloid Silicone Remover 7799 is a fast-evaporating organic solvent mixture used primarily to remove oil and grease residues on metal.

 Cleans metal substrates well before painting with solventborne paint products.

For professional use only!

Spies Hecker simply closer.



An Axalta Coating Systems Brand

VR Technical Data Sheet No. EN / 7799A.10 1 / 17.01.2024



Permaloid® Silicone Remover 7799

Product preparation - application Preparatory Cleaner



It is strongly recommended to use appropriate personal protection equipment during application to avoid respiratory, skin and eye irritation.





Old or original paintwork unsanded.

Old or original paintwork well sanded.

OEM Primer (e-coat), unsanded.

OEM Primer (e-coat), sanded.

Bare steel sanded.

Galvanised steel or soft aluminium sanded.

Glass fibre reinforced polyester substrates, free of release agents sanded.

Surfaces pretreated with 2K polyester products and then finely sanded.

Wipe dry with a clean cloth.

Change cloths often, never use dirty cloths.

Never let Permaloid® Silicone Remover 7799 evaporate from the surface. Treat only one small area at the time.

Degrease the sanded surface with Permaloid® Silicone Remover 7799 just before application of Undercoats or Topcoats.



Ready to use



Not applicable

VOC compliant

This product mix is not VOC compliant.

VR Technical Data Sheet No. EN / 7799A.10 2 / 17.01.2024



Permaloid® Silicone Remover 7799

Product preparation - application Final Cleaner



It is strongly recommended to use appropriate personal protection equipment during application to avoid respiratory, skin and eye irritation.





Old or original paintwork well sanded.

Glass fibre reinforced polyester substrates, free of release agents sanded.

Degrease the sanded surface with Permaloid® Silicone Remover 7799 just before application of Undercoats or Topcoats.

Wipe dry with a clean cloth.

Change cloths often, never use dirty cloths.

Never let Permaloid® Silicone Remover 7799 evaporate from the surface. Treat only one small area at the time.



Ready to use



Not applicable

VOC compliant

This product mix is not VOC compliant.

VR Technical Data Sheet No. EN / 7799A.10 3 / 17.01.2024



Permaloid® Silicone Remover 7799

Products

Permaloid® Silicone Remover 7799

Consult Safety Data Sheet prior to use. Observe the precautionary notices displayed on the container.

All other products referred to in the refinish build up are from our Spies Hecker product range. System properties will not be valid when the related material is used in combination with any other materials or additives which are not part of our Spies Hecker product range, unless explicitly indicated otherwise.

For professional use only! The information provided in this documentation has been carefully selected and arranged by us. It is based upon our best knowledge on the subject at the date of issuance. The Information is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check the information with regard to up-to-dateness and suitability for his intended purpose. The intellectual property in this Information, including patents, trademarks and copyrights, is protected. All rights reserved. The relevant Material Safety Data Sheet and Warnings displayed on the product label need to be observed. We may modify and/ or discontinue operation of all or portions of this Information at any time in our sole discretion, without notice and assume no responsibility to update the Information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.